






SANICUBIC® 2SC

SEWAGE LIFTING UNITS



SEWAGE
WC, bathroom, kitchen and laundry

22 m
↑



BENEFITS

- High performance: 2 single channel pumps in three phases
- Large container volume and switching volume
- Blockage-free operation by 80 mm (3.0 & 4.0 kW version) or 100 mm (5.5 & 7.5 kW version) solids handling
- Comfort control unit included in delivery


APPLICATIONS

- Drainage of domestic sewage from apartment buildings, residential areas, hospitals, schools etc.
- Institutions which need a continuous sewage drainage

FEATURES

- Polyethylene container
- Pump housing with flanged outlet bend DN 100
- Lateral inlet with loose-type flange DN 150
- Additional connection 1 1/2" for manual diaphragm pump
- Star-delta-start for 7,5 kW unit
- Operation temperature max. 55°C
- Operating mode S3 - 40%
- Alarm level adjustable

PUMP GRAPH



REFERENCE	EAN	FACTORY CODE	SYSTEM	TANK (L)	SWITCHING VOLUME(L)	UVI	P1 (W)	P2 (W)	FREQUENCY (Hz)	INOM (A)	TR/MIN	POWER CLASS	Q MAX (M³/H)	H MAX (M)	WEIGHT (KG)	REMOTE CONTROL	POWER CLASS CONTROL	ALARM
SANICUBIC 2 SC3.0 T	3 308 815 079 073	CUBIC25C3.0T	Single Channel	1,000	500	400	2x4,000	3,000	50/60	2x6.9	1,400	IP 57	120	10	370	ZPS2	IP 65	External wired
SANICUBIC 2 SC4.0 T	3 308 815 079 080	CUBIC25C4.0T					2x5,500	4,000		2x11.2			140	13	385			
SANICUBIC 2 SC5.5 T	3 308 815 079 097	CUBIC25C5.5T					2x6,300	5,500		2x12.1			160	18	400			
SANICUBIC 2 SC7.5 T	3 308 815 079 103	CUBIC25C7.5T					2x8,700	7,500		2x16.9			165	22	425			