



SANISUB°S ZPK



Particle size 10-30 mm Portable

Automatic release triggered by adjustable float Can handle water up to an average temperature of 90°C over a short period Pump for fast flowing or saline water (maximum salt content 15%)

grey water

10m power cable

Horizontal discharge 1 ¼ MPT

Float switch fitted as standard

APPLICATIONS


Pump for grey or rain water from cellars, garages or rainwater manholes

Portable pump for emergency pumping

Domestic grey water disposal (showers, washing machine, sinks)

Evacuation of brine water from softeners and fast flowing or saline water (max. 15%)

PUMP CURVE



PACKAGING

90° connection elbow pipe (30A DN25, 40A DN32)

10mm particle size for S ZPK 30A, 30mm for S ZPK 40A

FEATURES
Submersible polypropylene and stainless steel pump for

90° connection elbow

Pump

10m power cable with plug

REFERENCE	U (V)	P1 (W)	P2 (W)	FREQUENCY (HZ)	I MAX (A)	TR/MN	IP RATING	Q MAX (M³/H)	H MAX (M)	WEIGHT (KG)
SANISUB S ZPK 30 A	230	300	130	50-60	1.3	2,800	IP68	7	7.5	4.5
SANISUB S ZPK 40 A		850	430		3.7			10	10	6.5

APPLICATIONS



DISCHARGE HEIGHT



WARRANTY



ZehnderPumpen

Chnolo

Sanisub S ZPK 30A Product Code: SANISUB-003

Barcode: EAN 3308815081458

Sanisub S ZPK 40 A Product Code: SANISUB-004

Barcode: EAN 3308815081465

